







Braille XC15.0-750-2 Motorsport Lithium Battery

At only 3.0 KG, the XC15.0-750-2 Motorsport Lithium Battery is a high-performance upgrade from a traditional lead acid battery. Offering significant weight reduction, more power output and lasting up to 5 times longer than lead acid batteries!

BENEFITS:

- Superior starting capabilities with high cranking amp output per $\ensuremath{\mathsf{kg}}$
- Fast and efficient recharge, up to 5 times faster than lead acid batteries
- Can be used in "Total Loss" (no alternator) applications
- 3-5 times longer service life vs lead-acid batteries
- · Engineered for high shock and vibration applications
- Up to 2/3 weight reduction for equivalent cranking performance

750	3.0	15.0	192
10 SECONDS (A)	WEIGHT (KG)	CAPACITY (Ah)	CAPACITY (Wh)

PRODUCT INFORMATION

Physical Specs

Battery Chemistry	LFP
Length (mm)	248
Width (mm)	96
Height (mm)	154
Weight (kg)	3.0
Terminal Type	Brass terminal block with M6 bolt

Technical Specs

5	Second Pulse Cranking Amps	947	Charging Temperature	0C to 50C
) Second Pulse Discharge urrent (A)	750	Discharge	
	oltage	12	Temperature Range	-20C to +60C
C	apacity (Ah)	15.0	Storage Temperature	-20C to +60C
C	apacity (Wh)	192		
C	ontinuous Discharge Current (A)	300		

Charging

Polarity

Recharge Voltage	14.4V - 14.6V
Maintenance Charge Voltage	13.8V

Right +











Rev 05-23









