







Braille XC22.5-1250-C Motorsport Lithium Battery

At only 4.8 KG, the XC22.5-1250-C Motorsport Lithium Battery is a high-performance upgrade from a traditional lead acid battery. Offering significant weight reduction, more power output and lasting up to 5 times longer than lead acid batteries!

BENEFITS:

- Superior starting capabilities with high cranking amp output per kg
- Fast and efficient recharge, up to 5 times faster than lead acid batteries
- Can be used in "Total Loss" (no alternator) applications
- 3-5 times longer service life vs lead-acid batteries
- · Engineered for high shock and vibration applications
- Up to 2/3 weight reduction for equivalent cranking performance

1250	4.8	22.5	288
10 SECONDS (A)	WEIGHT (KG)	CAPACITY (Ah)	CAPACITY (Wh)

PRODUCT INFORMATION

Physical Specs

Battery Chemistry	LFP
Length (mm)	279
Width (mm)	173
Height (mm)	195
Weight (kg)	4.8

Terminal Type SAE terminals
Polarity Right +

Technical Specs

5 Second Pulse Cranking Amps	1520	Charging	0C to 50C
10 Second Pulse Discharge	1250	Temperature	0010300
Current (A)		Discharge Temperature Range	-20C to +60C
Voltage	12		
Capacity (Ah)	22.5	Storage Temperature	-20C to +60C
Capacity (Wh)	288		
Continuous Discharge Current (A)	500		

Charging

Recharge Voltage 14.4V - 14.6V
Maintenance Charge Voltage 13.8V











Rev 05-23









